



LED cijevi 9 W/18 W/24 W

Zamjena za fluorescentne cijevi

18 W/36 W/ 58 W

LED cijevi sa životnim vijekom 80000 h



Snaga	9 W	18 W	24 W
Napon	AC 90 – 305 V	AC 90 – 305 V	AC 90 – 305 V
Temperatura boje	2700 K – 6500 K	2700 K – 6500 K	2700 K – 6500 K
Kut svjetla	120°	120°	120°
Svjetlosni tok	900 lm	1800 lm	2400 lm
Uzvrat boje	80	80	80
Životni vijek	80 000 sati	80 000 sati	80 000 sati
Grlo	G13	G13	G13
Dimenzije	Ø26x600 mm	Ø26x1200 mm	Ø26x1500 mm
Radna temperatura	-20 – 40 °C	-20 – 40 °C	-20 – 40 °C
Materijal	Al + PC	Al + PC	Al + PC



LED cijevi 9 W/18 W/24 W

Zamjena za fluorescentne cijevi

18 W/36 W/ 58 W

LED cijevi s kutem svjetla 180°



Snaga	9 W	18 W	24 W
Napon	AC 185 – 265 V	AC 185 – 265 V	AC 185 – 265 V
Temperatura boje	2700 K – 6500 K	2700 K – 6500 K	2700 K – 6500 K
Kut svjetla	180°	180°	180°
Svjetlosni tok	828 – 900 lm	1656 – 1800 lm	2208 – 2400 lm
Uzvrat boje	≥80	≥80	≥80
Životni vijek	50 000 sati	50 000 sati	50 000 sati
Grlo	G13	G13	G13
Dimenzije	Ø26x600 mm	Ø26x1200 mm	Ø26x1500 mm
Radna temperatura	-20 – 60 °C	-20 – 60 °C	-20 – 60 °C
Materijal	Al + PC	Al + PC	Al + PC



LED cijevi 9 W/18 W/25 W

Zamjena za fluorescentne cijevi

18 W/36 W/ 58 W



Snaga	10 W	18 W	24 W
Napon	AC 100 – 240 V	AC 100 – 240 V	AC 100 – 240 V
Temperatura boje	2700 K – 6500 K	2700 K – 6500 K	2700 K – 6500 K
Kut svjetla	150°	150°	150°
Svjetlosni tok	900 lm	1650 lm	2250 lm
Uzvrat boje	≥75	≥75	≥75
Životni vijek	50 000 sati	50 000 sati	50 000 sati
Grlo	G13	G13	G13
Dimenzije	Ø26x600 mm	Ø26x1200 mm	Ø26x1500 mm
Radna temperatura	-20 – 45 °C	-20 – 45 °C	-20 – 45 °C
Materijal	Al + PC	Al + PC	Al + PC