



LED reflektori 10 W/ 30 W/ 50 W

Zamjena za metalhalogene reflektore

30 W/70 W/100 W



Snaga	10 W	30 W	50 W
Napon	AC 85 – 265 V	AC 85 – 265 V	AC 85 – 265 V
Temperatura boje	2700 K – 6500 K	2700 K – 6500 K	2700 K – 6500 K
Kut svjetla	120°	120°	120°
Svjetlosni tok	700 – 950 lm	2100 – 2850 lm	3500 – 4750 lm
Uzvrat boje	75	75	75
Životni vijek	50 000 sati	50 000 sati	50 000 sati
Dimenzije	115x85x80 mm	225x185x130 mm	285x235x150 mm
IP zaštita	IP65	IP65	IP65
Radna temperatura	-25 – 55 °C	-25 – 55 °C	-25 – 55 °C
Materijal	Al	Al	Al



LED reflektori 56 W/ 84 W/ 196 W

Zamjena za metalhalogene reflektore

150 W/250 W/400 W



Snaga	56 W	84 W	196 W
Napon	AC 110 – 265 V	AC 110 – 265 V	AC 110 – 265 V
Temperatura boje	2700 K – 6500 K	2700 K – 6500 K	2700 K – 6500 K
Kut svjetla	120°	120°	120°
Svjetlosni tok	5320 – 6720 lm	7980 – 10080 lm	18620 – 23520 lm
Uzvrat boje	75	75	75
Životni vijek	50 000 sati	50 000 sati	50 000 sati
Dimenzije	432x306x70 mm	552x306x70 mm	1032x306x70 mm
IP zaštita	IP65	IP65	IP65
Radna temperatura	-25 – 55 °C	-25 – 55 °C	-25 – 55 °C
Materijal	Al	Al	Al

- Dostupni u snagama: 28 W, 42 W, 56 W, 70 W, 84 W, 98 W 112 W, 126 W, 140 W, 154 W, 168 W, 182 W, 196 W



LED reflektori 70 W/ 100 W/ 200 W

Zamjena za metalhalogene reflektore

150 W/250 W/400 W



Snaga	70 W	100 W	200 W
Napon	AC 85 – 265 V	AC 85 – 265 V	AC 85 – 265 V
Temperatura boje	2700 K – 6500 K	2700 K – 6500 K	2700 K – 6500 K
Kut svjetla	120°	120°	120°
Svjetlosni tok	4900 – 6650 lm	7000 – 9500 lm	14000 – 19000 lm
Uzvrat boje	75	75	75
Životni vijek	50 000 sati	50 000 sati	50 000 sati
Dimenzije	290x250x116 mm	341x250x116 mm	400x340x121 mm
IP zaštita	IP65	IP65	IP65
Radna temperatura	-25 – 55 °C	-25 – 55 °C	-25 – 55 °C
Materijal	Al	Al	Al



LED reflektori cestovna rasvjeta

30 W/90 W

Zamjena za metalhalogene reflektore

70 W/250 W



Snaga	30 W	90 W
Napon	AC 110 - 265 V	AC 110 - 265 V
Temperatura boje	2700 K - 6500 K	2700 K - 6500 K
Kut svjetla	120°	120°
Svjetlosni tok	2850 - 3600 lm	8550 - 10800 lm
Uzvrat boje	75	75
Životni vijek	50 000 sati	50 000 sati
Dimenzije	530x250 mm	950x400 mm
IP zaštita	IP65	IP65
Radna temperatura	-25 - 55 °C	-25 - 55 °C
Materijal	Al	Al